

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number  
**WO 2005/042306 A2**

(51) International Patent Classification<sup>7</sup>: **B60R**  
(21) International Application Number:  
PCT/US2004/035017  
(22) International Filing Date: 22 October 2004 (22.10.2004)  
(25) Filing Language: English  
(26) Publication Language: English  
(30) Priority Data:  
60/513,644 23 October 2003 (23.10.2003) US

(71) Applicant (for all designated States except US): DELPHI  
TECHNOLOGIES, INC. [US/US]; P.O. Box 5052, Mail  
code 480-410-202, Troy, MI 48007-5052 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BRANDL, Michael,  
C. [US/US]; 461 Jennifer Lane, Grayslake, IL 60030 (US).  
BARTHEL, Richard, C. [US/US]; 33030 N. River Road,  
Libertyville, IL 60048 (US). NOVELLE, Anthony, J.  
[US/US]; 120 Newton Avenue, Glen Ellyn, IL 60137 (US).

(74) Agent: WOOD, David, P.; Delphi Technologies, Inc., P.O.  
Box 5052, Legal Staff-M/C 480-410-202, Troy, MI 48007-  
5052 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished  
upon receipt of that report

[Continued on next page]

(54) Title: CONTROL CARTRIDGE AND CONTROL HANDLE INCLUDING SAME



(57) Abstract: A control cartridge has a circuit board that includes a Hall effect sensor, the position of which is fixed in a housing that has a cam. The control cartridge includes a shaft that carries a magnet and that rotates and translates with respect to the housing. The shaft has a cam follower that engages the cam and translates the shaft with respect to the housing when the shaft is rotated with respect to the housing in one direction but not in an opposite direction. The control cartridge is shown as part of a control handle for a motorcycle in which the relative angular position of the shaft with respect to the Hall effect sensor is used to control engine speed manually while the relative axial position of the shaft with respect to the Hall effect sensor is used to deactivate a cruise control.

WO 2005/042306 A2